

(12) PATENT APPLICATION PUBLICATION

(21) Application No.202211064185 A

(19) INDIA

(43) Publication Date : 25/11/2022

(22) Date of filing of Application :10/11/2022

(54) Title of the invention : SECURED KEY HOLDING DEVICE

(51) International classification :H04L0009080000, H04L0009320000, G01S0017480000, F25D0029000000, A45C0011320000
(86) International Application No :NA
Filing Date :NA
(87) International Publication No : NA
(61) Patent of Addition to Application Number :NA
Filing Date :NA
(62) Divisional to Application Number :NA
Filing Date :NA

(71)Name of Applicant :

1)Jaipur National University

Address of Applicant :Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

Name of Applicant : NA

Address of Applicant : NA

(72)Name of Inventor :

1)Raminder Singh

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

2)Vatsala Pawar

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

3)Isha Srivastava

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

4)Anu Singh

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

(57) Abstract :

A secured key holding device, comprises of a circular frame 1 adapted to be held by a user, multiple number of motorized clamps 2 arranged on the frame 1 for gripping multiple keys that are placed by the user within the clamps 2, a biometric scanner 3 installed on the frame 1 for authenticating the user, an artificial intelligence based image capturing module 4 for capturing images of the frame's 1 surrounding, respectively to detect a type of lock present in proximity to the frame 1, a sliding unit 5 coupled between the clamps 2 and frame 1 for aligning one of the clamps 2 accommodating that specific key that is required to open the specific type of lock.

No. of Pages : 12 No. of Claims : 4

Registrar
Jaipur National University