

(12) PATENT APPLICATION PUBLICATION

(21) Application No.202211064786 A

(19) INDIA

(22) Date of filing of Application :11/11/2022

(43) Publication Date : 25/11/2022

(54) Title of the invention : POOLSIDE AMUSEMENT DEVICE

(51) International classification :B60N0002700000, H01M0010625000, F16M0013020000, F16M0011180000, F16M0011040000
(86) International Application No :NA
Filing Date :NA
(87) International Publication No : NA
(61) Patent of Addition to Application Number :NA
Filing Date :NA
(62) Divisional to Application Number :NA
Filing Date :NA

(71)Name of Applicant :

1)Jaipur National University

Address of Applicant :Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

Name of Applicant : NA

Address of Applicant : NA

(72)Name of Inventor :

1)Sanjeet Kumar

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

2)Surbhi Agrawal

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

3)Surendra Mehra

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

4)Urmimala Naha

Address of Applicant :School of Engineering & Technology, Jaipur National University, Jaipur-Agra Bypass, Near New RTO office, Jagatpura, Jaipur-302017, Rajasthan, India. Jaipur -----

(57) Abstract :

A poolside amusement device comprising of a C-shaped extendable frame 1 having a first and second end 2,3 which is positioned at a side of reservoir for performing activities, touch enabled screen 5 is mapped on frame 1 for selecting activity, artificial intelligence module 5 is mounted on frame 1 for capturing images of the frame 1, bars 7 are configured on the frame 1 for maneuvering user from one to the other end, spring 9 is configured between plate 8 and frame 1 for allowing user to jump into reservoir, telescopically operated rod 10 equipped with cushion pad 11 is suspended from the frame 1 for performing swinging activity, motorized slider 14 is configured between frame 1 and rod 10 for providing motion to cushion pad 11, motorized ball and socket joint 12 is coupled between rod 10 and frame 1 for providing rotational movement to cushion pad 11.

No. of Pages : 16 No. of Claims : 10



Registrar
Jaipur National University